

VI - DIRECTIONS IN PROPULSION CONTROL

Carl F. Lorenzo

This section discusses research at NASA Lewis in the area of propulsion controls as driven by trends in advanced aircraft. The objective of the Lewis program is to develop the technology for advanced reliable propulsion control systems and to integrate the propulsion control with the flight control for optimal full-system performance.

CONTEMPORARY PROPULSION CONTROLS ISSUES

The primary drivers seen for propulsion control research are a continuing increase in aircraft and propulsion system complexity, increased dynamic coupling between the aircraft and the propulsion system, and a continuing need to reduce control system weight while increasing reliability.

The demand for increased functionality for future aircraft and the desire to optimize aircraft and propulsion systems as an integrated entity has led to a large increase in the physical complexity of the aircraft/propulsion systems. The new functionalities can include vertical and short-takeoff-and-landing capabilities coupled with high-speed cruise. To achieve these capabilities special-purpose aircraft are being designed with a high degree of dynamic coupling between aircraft and propulsion systems. This is a dramatic departure from traditional aircraft design where such coupling was minimized. The effect of large dynamic coupling is to increase pilot work load. Advanced controls can help alleviate the problem of pilot work load and allow optimal aircraft performance to be achieved; however, this necessitates that the unified or integrated design approach to aircraft flight controls and propulsion control be evolved.

Control weight as a percentage of propulsion system weight is significant in spite of gains made by conversion to digital systems. Previous sections of this paper have discussed our efforts in fiber optics and high-temperature electronics (using silicon carbide), which should help reduce control system weight. Further efforts are perhaps best approached by industry as part of the design process and by applying new materials technologies.

COMPLEXITY ISSUE

Airbreathing engine complexity is reflected by the number of primary control variables managed for a given engine (fig. VI-1). This is an important measure, since it indicates the number of sensors required as well as the amount of actuation, and it is a general indicator of propulsion system complexity. The trend has shown a steady increase in controlled variables over

the years. With this trend has come the use of full-authority digital electronic controllers, which have helped in dealing with the complexity issue. The increase in control components implies a corresponding decrease in control reliability unless specific measures are taken to deal with the issue.

DYNAMIC COUPLING

Typical of aircraft with significant dynamic coupling are supersonic short takeoff and vertical landing aircraft (STOVL) (fig. VI-2), advanced high-speed x-wing rotor craft, and even hypersonic aircraft where engine air capture and aircraft pitch control are tightly coupled. Vertical lift aircraft flight control at low forward speed and through transition are typically dominated by propulsion control considerations. These aspects provide strong motivation for research in the area of flight/propulsion control integration.

PROPULSION CONTROLS

Current activities of the NASA Lewis controls research program are indicated as follows:

- (1) Hypersonic propulsion dynamics and control
- (2) Reconfigurable control
- (3) Controls networking
- (4) Sensor failure detection, isolation, and accommodation

The hypersonic propulsion control work includes hypersonic engine dynamic modeling, propulsion control, and control instrumentation keyed to the NASP technology maturation program. Dynamic models of the various NASP components are being developed (refs. VI-1 to VI-4) and integrated into full engine models for study of dynamic ramjet/scramjet stability and control. Several dynamic inlet models, which include inlet unstart studies, have been implemented, and combustor models consistent with real-time simulation have been formulated.

The reconfigurable control effort seeks to create expert system intelligence which, in real time, can "redesign" a control system to account for significant changes in aircraft or engine behavior. In this process (fig. VI-3) an on-line recursive identifier will monitor the plant variables to detect changes in the plant. When such a change occurs an expert system (ref. VI-5) will be invoked to manage a control redesign using one of several design approaches. The new design will be impressed on the plant controller. If necessary, a second expert system (yet to be developed) will tune the control for desired performance.

Efforts in controls networking aim to develop high-performance communications systems tailored specifically to distributed integrated aircraft flight/propulsion controls. The magnitude and the time variability of network-induced delay directly impacts control system stability. Thus, network performance, that is, end-to-end delay as a function of offered load and communications packet size, for various configurations has been both simulated and measured directly from network systems for various configurations (refs. VI-6 to VI-12). Further, to improve control tolerance of delay, the use of filters and observers, and control synchronization across the distributed control system are being studied (refs. VI-13 to VI-16).

FAILURE DETECTION ISOLATION AND ACCOMMODATION

The Sensor Failure Detection and Accommodation program (refs. VI-17 to VI-28) strives to attain control system reliability through the application of analytical redundancy instead of hardware redundancy (multiple sensors for each measurement). Analytical redundancy uses available sensor information and reference models of the engine to detect sensor failures and to generate accurate estimates which replace failed sensor information to the controller (fig. VI-4).

Sensor failure accommodation logic has been developed that uses sensed signals from the engine and actuators together with analytical models of the engine to create (Kalman filter based) estimates of the engine parameters. These estimates (fig. VI-5) are used by the multivariable control as representing the actual engine variables. Failed sensors are detected by "hypothesis testing" a series of hypothesis filters, each of which uses all available signals but one. Likelihood statistics are generated and compared to detect the failed sensor(s). The failed sensors are then removed from the calculation of the estimates.

The sensor failure accommodation algorithm and multivariable controller are implemented (fig. VI-6) in a triple-microprocessor-based control system (ref. VI-24). The computers calculate (1) the multivariable control laws, (2) the detection and accommodation logic, and (3) the isolation logic to determine which sensors have failed. The processors are Intel 80186/80187 based hardware which allow a 40-msec update time while processing the algorithms in a high-level language (FORTRAN). This computer implementation was used to validate the detection and accommodation logic both for real-time simulations and with an actual engine.

To validate the analytical formulation and practical implementation of the sensor failure algorithm, full-scale tests were performed (ref. VI-22) with the Pratt & Whitney F-100 engine in the Lewis Propulsion System Laboratory (fig. VI-7). The tests were conducted over a wide range of altitude/Mach number conditions.

In the tests, various forms of sensor failure were electronically imposed on the control sensors. Actual engine performance in response to an imposed drift failure in the nozzle pressure sensor signal is shown in figure VI-8. Such small drift failures are very difficult to detect, and thus the time of detection is not immediate. It can be seen, however, that the actual engine thrust loss is quite small. In the figure the "sensed" variable is the signal that would be normally seen by the control. The "actual" is the "sensed" variable without the imposed drift failure, and the "estimated" is nozzle pressure as determined by the Kalman filter.

The major events are as follows: at point A, a slow drift is introduced into the sensed signal, so that sensed signal would begin to deviate at a rate of 1 psi/sec. From point A to point B, the control tries to accommodate what is going on. It senses the pressure rising and opens up the nozzle area. In response to that the actual pressure begins to fall, until a loss of control authority at point B. At that point the sensed pressure begins to deviate at the 1 psi/sec rate. At point C the logic has determined that failure has occurred and removes the faulty sensed variable, in this case, nozzle pressure,

from the estimator calculation. Then the actual signal and the estimate begin to come back together as the control returns to a normal mode operation. At point E, without sensor failure accommodation, engine shutoff occurs.

The results of the sensor failure accommodation testing on the F-100 engine are summarized as follows:

- (1) High-performance failure detection (120 different failure scenarios, 11 engine operating conditions, both subsonic and supersonic conditions)
- (2) Good post-failure accommodation performance (no significant loss of performance power transients with accommodated failures)
- (3) Sequential failure detection and accommodation
- (4) Simultaneous failure detection and accommodation
- (5) Engine control with all feedback sensors failed

One hundred and twenty different failure scenarios were run. Demonstrated capabilities include the detection, isolation, and accommodation of drift, in-range step, noise, and large-scale "hard" failures. Failure testing was done at 11 Mach number/altitude operating conditions over the flight envelope. Also demonstrated was the capability to detect sequential sensor failures as well as simultaneous failures. The algorithm worked satisfactorily for all tests. Excellent post-failure control performance was demonstrated including full-range operation with single sensor failure.

As a demonstration case the F-100 engine was run with all feedback sensors failed. (The input sensors Pt_2 and Tt_2 were not failed.) Under the condition of all engine control sensors failed, the controller correctly detected each failure and accommodated all failures by using the computed estimates for all the signals. While in this condition the engine was smoothly accelerated and decelerated as shown in figure VI-9.

The NASA Lewis new thrusts in propulsion control are focused on the areas of supersonic STOVL integrated control and intelligent system control.


INTEGRATED FLIGHT/PROPULSION CONTROL

The supersonic STOVL aircraft (fig. VI-10) typifies the trend toward complex aircraft with large dynamic coupling between the aircraft and propulsion system. A NASA Lewis and NASA Ames program will develop advanced integrated controls methodologies and designs for this application. Current plans focus on the F-16 aircraft and the F-110 engine with vectorable nozzles and an ejector as the vertical thrust effector. The integration problem is to evolve controls designs and methodologies which integrate subsystem controls in a manner to achieve optimal aircraft performance. Nonlinear simulation models of both aircraft and propulsion system are being created. Linear control models will be abstracted from these to be used as a basis for control design. Validation tests at NASA Lewis will incorporate a piloted simulator and actual engine/ejector firing together with a simulated aircraft to evaluate developed control laws. Final validation is planned to be done with the NASA Ames Vertical Motion Simulator.

INTELLIGENT SYSTEM CONTROL

The block diagram in figure VI-11 indicates an expansion of the traditional control function into a broad system intelligence (ref. VI-29). This will be initially applied to reusable space propulsion systems. The inner control loop will be designed with life-extending methodologies (yet to be developed) which will combine controls technologies with those of structure and material sciences. The new interdisciplinary technology will be applied to state-of-the-art engines such as space shuttle main engine or hypersonic propulsion systems where transient effects on engine life are important, and where transient performance must be controlled.

Artificial intelligence concepts will likely be used for the highlighted functions. An on-board diagnostic/prognostic expert system will identify impending hardware failures using information from component condition monitoring instruments, and engine dynamics monitor and performance information. A high-level coordinator will determine the required remedial action; for example, change control request or if necessary invoke a control adapter that will reconfigure (redesign) the control in flight. This research is expected to greatly enhance vehicle and propulsion performance, and substantially improve life, reliability, and maintainability.



CD-87-29841

Figure VI-1. - Trends in control complexity of aircraft turbine engines.



CD-87-29842

Figure VI-2. - Supersonic short takeoff and vertical landing aircraft.




Figure VI-3. - Block diagram of reconfigurable control system.






Figure VI-4. - Analytical redundancy.




CD-87-29845

Figure VI-5. - Simplified block diagram for sensor failure accommodation system.




CD-87-29846

Figure VI-6. - Hardware implementation for sensor failure accommodation system.




CD-87-29847

Figure VI-7. - Pratt & Whitney F-100 as used in sensor failure accommodation program in Propulsion Systems Laboratory.



CD-87-29848

Figure VI-8. - F-100 engine drift failure on nozzle pressure.



CD-87-29849

Figure VI-9. - Engine response to throttle transient with all sensors failed.




Figure VI-10. - Supersonic STOVL ground test aircraft to be used in integrated controls studies.




Figure VI-11. - Block diagram of intelligent system control.

VII - INSTRUMENTATION AND CONTROLS RESEARCH REFERENCES

Research Sensors

- II-1. Elmore, D.L.; Robinson, W.W.; and Watkins, W.B.: Dynamic Gas Temperature Measurement System. Instrumentation in the Aerospace Industry, Vol. 30, Advances in Test Measurements, Vol. 21, Instrument Society of America, Research Triangle Park, NC, 1984, pp. 289-302.
- II-2. Elmore, D.L.; Robinson, W.W.; and Watkins, W.B.: Dynamic Gas Temperature Measurement System, Vol. I, Technical Efforts. (PWA/GPD-FR-17145-VOL-1, Pratt and Whitney Aircraft; NASA Contract NAS3-23154) NASA CR-168267-VOL-1, 1983.
- II-3. Elmore, D.L.; Robinson, W.W.; and Watkins, W.B.: Further Development of the Dynamic Gas Temperature Measurement System, Volume I, Technical Efforts. (P&W/GPD FR-19381-VOL-1, Pratt and Whitney; NASA Contract NAS3-24228) NASA CR-179513-VOL-1, 1986.
- II-4. Stocks, D.R.; and Elmore, D.L.: Further Development of the Dynamic Gas Temperature Measurement System, Vol. II, Computer Program User's Manual. (P&W/GPD-FR-19381-VOL-2, Pratt and Whitney Aircraft; NASA Contract NAS3-24228) NASA CR 179513-VOL-2 (Also listed as NASA CR-179604), 1986.
- II-5. Atkinson, W.H.; Hobart, H.F.; and Strange, R.R.: Advanced High Temperature Heat Flux Sensors. Advances in Instrumentation, Vol. 38, Part 2, Instrument Society of America, Research Triangle Park, NC, 1983, pp. 1457-1479.
- II-6. Atkinson, W.H.; and Strange, R.R.: Development of Advanced High-Temperature Heat Flux Sensors. (PWA-5723-27, Pratt and Whitney Aircraft; NASA Contract NAS3-22133) NASA CR-165618, 1982.
- II-7. Atkinson, W.H.; Cyr, M.A.; and Strange, R.R.: Development of High-Temperature Heat Flux Sensors, Phase II, Verification Testing. (PWA-5914-39, Pratt and Whitney Aircraft; NASA Contract NAS3-22133) NASA CR-174973, 1985.
- II-8. Atkinson, W.H.; Cyr, M.A.; and Strange, R.R.: Turbine Blade and Vane Heat Flux Sensor Development, Phase 1. (PWA-5914-21, Pratt and Whitney Aircraft; NASA Contract NAS3-23529) NASA CR-168297, 1984.
- II-9. Atkinson, W.H.; Cyr, M.A.; and Strange, R.R.: Turbine Blade and Vane Heat Flux Sensor Development, Phase 2. (PWA-5914-39, Pratt and Whitney Aircraft; NASA Contract NAS3-23529) NASA CR-174995, 1985.
- II-10. Holanda, R.: Analysis of Thermoelectric Properties of High-Temperature Complex Alloys of Nickel-Base, Iron-Base, and Cobalt-Base Groups. NASA TP-2278, 1984.

- II-11. Grant, H.P.; and Przybyszewski, J.S.: Thin Film Temperature Sensor. (PWA-5526-31, Pratt and Whitney Aircraft; NASA Contract NAS3-20768) NASA CR-159782, 1980.
- II-12. Grant, H.P.; Przybyszewski, J.S.; and Claing, R.G.: Turbine Blade Temperature Measurements Using Thin Film Temperature Sensors. (PWA-5604-31, Pratt and Whitney Aircraft; NASA Contract NAS3-20831) NASA CR-165201, 1981.
- II-13. Grant, H.P., et al.: Thin Film Temperature Sensors, Phase III for Engine-Test Evaluation (PWA-5708-26, Pratt and Whitney Aircraft; NASA Contract NAS3-22002) NASA CR-165476, 1982.
- II-14. Liebert, C.H., et al.: High Temperature Thermocouple and Heat Flux Gage Using a Unique Thin Film-Hardware Hot Junction. J. Eng. Gas Turbines Power, vol. 107, no. 4, Oct. 1985, pp. 938-944 (NASA TM-86898).
- II-15. Kreider, K.G.; Semancik S.; and Olson, C.: Advanced Thin Film Thermocouples. (NBSIR 84-2949, National Bureau of Standards) NASA CR-175541, 1984.
- II-16. Kreider, K.G.; and Semancik, S.: Thermal and Sputtered Aluminum Oxide Coatings for High Temperature Electrical Insulation. J. Vac. Sci. Technol. A, vol. 3, no. 6, Nov./Dec. 1985, pp. 2582-2587.
- II-17. Prakash, S., et al.: Pretreatment Effects on the Morphology and Properties of Aluminum Oxide Thermally Grown on NiCoCrAlY. J. Vac. Sci. Technol. A, vol. 3, no. 6, Nov./Dec. 1985, pp. 2551-2556.
- II-18. Budhani, R.C.; Prakash, S.; and Bunshah, R.F.: Thin-Film Temperature Sensors for Gas Turbine Engines: Problems and Prospects. J. Vac. Sci. Technol. A, vol. 4, no. 6, Nov./Dec. 1986, pp. 2609-2617.
- II-19. Budhani, R.C., et al.: Oxygen Enhanced Adhesion of Platinum Films Deposited on Thermally Grown Alumina Surfaces. J. Vac. Sci. Technol. A, vol. 4, no. 6, Nov.-Dec. 1986, pp. 3023-3024.
- II-20. Hulse, C.O.; Bailey, R.S.; and Lemkey, F.D.: High Temperature Static Strain Gage Alloy Development Program. (R85-915952-13, United Technologies Research Center; NASA Contract NAS3-23169) NASA CR-174833, 1985.
- II-21. Hulse, C.O., et al.: High Temperature Static Strain Gage Development Contract, Tasks 1 and 2. (R87-916527-1, United Technologies Research Center; NASA Contract NAS3-23722) NASA CR-180811, 1987.
- II-22. Hulse, C.O., et al.: Advanced High Temperature Static Strain Sensor Development. (R86-995875-28, United Technologies Research Center; NASA Contract NAS3-22126) NASA CR-179520, 1987.
- II-23. Stetson, K.A.: Demonstration Test of Burner Liner Strain Measuring System. (R84-926376-15, United Technologies Research Center; NASA Contract NAS3-23690) NASA CR-174743, 1984.
- II-24. Hobart, H.F.: Evaluation Results of the 700°C Chinese Strain Gages for Gas Turbine Engines. NASA TM-86973, 1985.

- II-25. Stetson, K.A.: The Use of Heterodyne Speckle Photogrammetry to Measure High-Temperature Strain Distributions. Holographic Data Nondestructive Testing, D. Vukicevic, ed., SPIE Proc. Vol. 370, Society of Photo-Optical Instrumentation Engineers, Bellingham, WA, 1983, pp. 46-55.
- II-26. Lant, C.T.; and Qaqish, W.: Optical Strain Measurement System Development-Phase I. NASA CR-179619, 1987.
- II-27. Lant, C.T.; and Qaqish, W.: Optical Strain Measurement System Development. NASA CR-179646, 1987.
- II-28. Atkinson, W.H.; Cyr, M.A.; and Strange R.R.: Development of Sensors for Ceramic Components in Advanced Propulsion Systems. (PWA-6113-12, Pratt and Whitney Aircraft; NASA Contract NAS3-25141) NASA CR-182111, 1988.
- II-29. Bennethum, W.H.; and Sherwood, L.T.: Sensors for Ceramic Components in Advanced Propulsion Systems. NASA CR-180900, 1988.

Optical Measurement Systems

- III-1. Decker, A.J.: Advanced Optical Measuring Systems for Measuring the Properties of Fluids and Structures. NASA TM-88829, 1986.
- III-2. Decker, A.J.; Beam-Modulation Methods in Quantitative and Flow-Visualization Holographic Interferometry. NASA TM-87306, 1986.
- III-3. Decker, A.J.; and Stricker, J.: A Comparison of Electronic Heterodyne Moire Deflectometry and Electronic Heterodyne Holographic Interferometry for Flow Measurements. SAE Paper 851896, 1985 (NASA TM-87071).
- III-4. Seasholtz, R.G.; Oberle, L.G.; and Weikle, D.H.: Optimization of Fringe-Type Laser Anemometers for Turbine Engine Component Testing. AIAA Paper 84-1459, June 1984 (NASA TM-83658).
- III-5. Seasholtz, R.G.: Application of Laser Anemometry in Turbine Engine Research. NASA TM-83513, 1983.
- III-6. Pelaccio, D.G.: Investigation of Laser Anemometry for Space Shuttle Main Engine Model Verification Experiments. (RI/RD86-163, Rockwell International; NASA Contract NAS3-24356) NASA CR-179470, 1986.
- III-7. Seasholtz, R.G.; and Goldman, L.J.: Combined Fringe and Fabry-Perot Laser Anemometer for Three-Component Velocity Measurements in Turbine Stator Cascade Facility. NASA TM-87322, 1986.
- III-8. Wernet, M.P.; and Edwards, R.V.: Implementation of a New Type of Time-of-Flight Laser Anemometer. Appl. Opt., vol. 25, no. 5, Mar. 1, 1986, pp. 644-648.
- III-9. Wernet, M.P.; and Oberle, L.G.: Laser Anemometry Techniques for Turbine Applications. ASME Paper 87-GT-241, 1987 (NASA TM-88953).
- III-10. Morey, W.W.: Hot Section Viewing System. (R84-925830-33, United Technologies Corp.; NASA Contract NAS3-23156) NASA CR-174773, 1984.

- III-11. Howes, W.L.: Rainbow Schlieren. NASA TP-2166, 1983.
- III-12. Howes, W.L.: Rainbow Schlieren and Its Applications. Appl. Opt., vol. 23, no. 14, July 15, 1984, pp. 2449-2460.
- III-13. Howes, W.L.: Rainbow Schlieren vs Mach-Zehnder Interferometer: A Comparison. Appl. Opt., vol. 24, no. 6, Mar. 15, 1985, pp. 816-822.
- III-14. Hovenac, E.A.: Performance and Operating Envelope of Imaging and Scattering Particle Sizing Instruments. Focus on Electro-Optic Sensing and Measurement (ICALEO 1987), G. Kychakoff, ed., Springer-Verlag, 1988.
- III-15. Hovenac, E.A.: Calibration of Droplet Sizing and Liquid Water Content Instruments: Survey and Analysis. (FAA/CT-86-19, Sverdrup Technology Inc.; NASA Contract NAS3-24105) NASA CR-175099, 1986.
- III-16. Hovenac, E.A.: Use of Rotating Reticles for Calibration of Single Particle Counters. The Changing Frontiers of Optical Techniques for Industrial Measurement and Control (ICALEO 1986), C.M. Penney and H.J. Caulfield, eds., Springer-Verlag, 1987, pp. 129-134.
- III-17. Hovenac, E.A.; Hirleman, E.D.; and Ide, R.F.: Calibration and Sample Volume Characterization of PMS Optical Array Probes. 3rd International Conference on Liquid Atomisation and Spray Systems (ICLASS 1985), P. Eisenklam and A. Yule, eds., Institute of Energy, London, England, 1985.

High-Temperature Electronics

- IV-1. Nieberding, W.C.; and Powell, J.A.: High Temperature Electronic Requirements in Aeropropulsion Systems. IEEE Trans. Industrial Electronics, vol. 29, no. 2, May 1982, pp. 103-106.
- IV-2. Powell, J.A.: Crystal Growth of 2H Silicon Carbide. J. Appl. Phys., vol. 40, no. 11, Oct. 1969, pp. 4660-4662.
- IV-3. Powell, J.A.: Refractive Index and Birefringence of 2H Silicon Carbide. J. Opt. Soc. Am., vol. 62, no. 3, Mar. 1972, pp. 341-344.
- IV-4. Powell, J.A.; and Will, H.A.: Low-Temperature Solid-State Phase Transformations in 2H Silicon Carbide. J. Appl. Phys., vol. 43, no. 4, Apr. 1972, pp. 1400-1408.
- IV-5. Powell, J. A.; and Will, H. A.: Epitaxial Growth of 6H SiC in the Temperature Range 1320°-1390°C. J. Appl. Phys., vol. 44, no. 11, Nov. 1973, pp. 5177-5178.
- IV-6. Powell, J.A.; and Will, H.A.: Process for Fabricating SiC Semiconductor Devices. U.S. Patent No. 3,956,032, May 11, 1976.
- IV-7. Nishino, S.; Powell, J.A.; and Will, H.A.: Production of Large-Area Single-Crystal Wafers of Cubic SiC for Semiconductor Devices. Appl. Phys. Lett., vol. 42, no. 5, Mar. 1, 1983, pp. 460-462.

- IV-8. Harris, G.L., et al.: Low-Pressure Growth of Single-Crystal Silicon Carbide. *Mater. Lett.*, vol. 4, no. 2, Feb. 1986, pp. 77-80.
- IV-9. Powell, J.A.; Matus, L.G.; and Kuczmariski, M.A.: Growth and Characterization of Cubic SiC Single-Crystal Films on Si. *J. Electrochem. Soc.*, vol. 134, no. 6, June 1987, pp. 1558-1565.
- IV-10. Chorey, C.M., et al.: TEM Investigation of Beta-SiC Grown Epitaxially on Si Substrate by CVD. *Semiconductor-Based Heterostructures: Interfacial Structure and Stability*, M.L. Green, et al., eds., The Metallurgical Society, Warrendale, PA, 1986, pp. 115-125.
- IV-11. Pirouz, P., et al.: Lattice Defects in Beta-SiC Grown Epitaxially on Silicon Substrates. *Heteroepitaxy on Silicon II*, J.C.C. Fan, J.M. Phillips, B.-Y. Tsaur, eds., MRS Symp. Proc. Vol. 91, Materials Research Society, Pittsburgh, PA, 1987, pp. 399-404.
- IV-12. Pirouz, P.; Chorey, C.M.; and Powell, J.A.: Antiphase Boundaries in Epitaxially Grown Beta-SiC. *Appl. Phys. Lett.*, vol. 50, no. 4, Jan. 26, 1987, pp. 221-223.
- IV-13. Powell, J.A., et al.: Improved Beta-SiC Heteroepitaxial Films Using Off-Axis Si Substrates. *Appl. Phys. Lett.*, vol. 51, no. 11, Sept. 14, 1987, pp. 823-825.
- IV-14. Choyke, W.J.; Feng, Z.C.; and Powell, J.A.: Low Temperature Photoluminescence Studies on Chemical-Vapor-Deposition-Grown 3C-SiC on Si. *J. Appl. Phys.*, vol. 64, no. 6, Sept. 15, 1988, pp. 3163-3175.
- IV-15. Feng, Z.C., et al.: Raman Scattering Studies of Chemical-Vapor-Deposited Cubic SiC Films on (100)Si. *J. Appl. Phys.*, vol. 64, no. 6, Sept. 15, 1988, pp. 3176-3186.
- IV-16. Feng, Z.C.; Choyke, W.J.; and Powell, J.A.: Raman Determination of Layer Stresses and Strains for Heterostructures and its Application to the Cubic SiC/Si System. *J. Appl. Phys.*, vol. 64, no. 12, Dec. 15, 1988, pp. 6827-6835.
- IV-17. Zhou, P.Z., et al.: Observation of Deep Levels in Cubic Silicon Carbide. *Appl. Phys. Lett.*, vol. 50, no. 19, May 11, 1987, pp. 1384-1385.
- IV-18. Segall, B., et al.: Compensation in Epitaxial Cubic SiC Films. *Appl. Phys. Lett.*, vol. 49, no. 10, Sept. 8, 1986, pp. 584-586.
- IV-19. Avila, R.E.; Kopanski, J.J.; and Fung, C.D.: Behavior of Ion-Implanted Junction Diodes in 3C-SiC. *J. Appl. Phys.*, vol. 62, no. 8, Oct. 15, 1987, pp. 3469-3471.
- IV-20. Fung, C.D.; and Kopanski, J.J.: Thermal Oxidation of 3C Silicon Carbide Single Crystal Layers on Silicon. *Appl. Phys. Lett.*, vol. 45, no. 7, Oct. 1, 1984, pp. 757-759.
- IV-21. Avila, R.E.; Kopanski, J.J.; and Fung, C.D.: Behavior of Inversion Layers in 3C Silicon Carbide. *Appl. Phys. Lett.*, vol. 49, no. 6, Aug. 11, 1986, pp. 334-336.

- IV-22. Dayan, M.: AES and LEED Study of the Zinc Blende SiC(100) Surface. J. Vac. Sci. Technol. A, vol. 3, no. 2, Mar.-Apr. 1985, pp. 361-366.
- IV-23. Wheeler, D.R.; and Pepper, S.V.: Angle-Resolved X-Ray Photoelectron Spectroscopy of Epitaxially Grown (100) Beta-SiC to 1300°C", Surf. and Interface Anal., vol. 10, no. 2-3, Mar. 1987, pp. 153-162.
- IV-24. Bellina, J.J., Jr.; and Zeller, M.V.: Stoichiometric Changes in the Surface of (100) Cubic SiC Caused by Ion Bombardment and Annealing. Appl. Surf. Sci., vol. 25, 1986, pp. 380-390.
- IV-25. Bellina, J.J., Jr.; Ferrante, J.; and Zeller, M.V.: Surface Modification Strategies for (100)3C-SiC. J. Vac. Sci. Technol. A, vol. 4, no. 3, May-June 1986, pp. 1692-1695.
- IV-26. Bellina, J.J., Jr.; and Zeller, M.V.: Thermally Activated Reactions of Titanium Thin Films with (100) 3C-SiC Substrates. Novel Refractory Semiconductors, D. Emin, T.L. Aselage, and C. Wood, eds., MRS Symp. Proc. Vol. 97, Materials Research Society, Pittsburgh, PA, 1987, pp. 265-270.
- IV-27. Zeller, M.V., et al.: AES Studies of the M/SiC Interface with Metal Carbide Formers. Novel Refractory Semiconductors, D. Emin, T.L. Aselage, and C. Wood, eds, MRS Symp. Proc. Vol. 97, Materials Research Society, Pittsburgh, PA, 1987, pp. 283-288.
- IV-28. Stinespring, C.D.; and Wormhoudt, J.C.: Gas Phase Kinetics Analysis and Implications for Silicon Carbide Chemical Vapor Deposition. J. Cryst. Growth, vol. 87, no. 4, Mar. 1988, pp. 481-493.

Fiber Optics for Controls

- V-1. Poumakis, D.J.; and Davies, W.: Fiber Optic Control System Integration. NASA CR-179569, 1986.
- V-2. Poppel, G.L.; Glasheen, W.M.; and Russell, J.C.: Fiber Optic Control System Integration. (R87AEB111, General Electric Co.; NASA Contract NAS3-24624) NASA CR-179568, 1987.
- V-3. Baumbick, R.J.: Fiber Optic Sensors for Measuring Angular Position and Rotational Speed. NASA TM-81454, 1980.
- V-4. Baumbick, R.J.: Fiber Optics for Aircraft Engine/Inlet Control. NASA TM-82654, 1981.
- V-5. Poppel, G.L.; Marple, D.T.F.; and Kingsley, J.D.: Analysis, Design, Fabrication and Testing of an Optical Tip Clearance Sensor. (R81AEG215, General Electric Co.; NASA Contract NAS3-21843) NASA CR-165265, 1981.
- V-6. Design, Fabrication and Testing of an Optical Temperature Sensor for High Temperature Control Applications. (United Technologies Research Center, NASA Contract NAS3-22774) NASA CR-174698, 1983.

- V-7. James, K.; and Quick, B.: Fiber-Optic, Fabry-Perot Temperature Sensor. NASA CR-174712, 1984.
- V-8. Berak, J.M.; Grantham, D.H.; and Eder, M.: Optical Switching of High Temperature GaAs Devices for Digital Control of Aircraft Direct-Drive Actuators. (UTRC-R86-926733-27, United Technologies Corp.; NASA Contract NAS4-24219) NASA CR-179465, 1986.
- V-9. Mossey, P.W.; Shafferknocker, W.M.; and Mulukutla, A.R.: 1700°C Optical Temperature Sensor. (R86AEB267, General Electric; NASA Contract NAS3-24085) NASA CR-175108, 1986.
- V-10. Glenn, W.H.; Morey, W.W.; and Snitzer, E.: Analysis and Preliminary Design of Optical Sensors for Propulsion Control. (R79-924112-14, United Technologies Research Center; NASA Contract NAS3-21004) NASA CR-159468, 1979.
- V-11. Baumbick, R.J., et al.: Optical Sensors for Aeronautics and Space. NASA TM-81407, 1980.
- V-12. Fritsch, K.; and Adamovsky, G.: Simple Circuit for Feedback Stabilization of a Single-Mode Optical Fiber Interferometer. Rev. Sci. Instrum., vol. 52, no. 7, July 1981, pp. 996-1000.
- V-13. Carome, E.F.; and Adamovsky, G.: High Kilohertz Frequency Fiber Optic Phase Modulators. Fiber-Optic Rotation Sensors and Related Technologies, Springer Series in Optical Sciences, Vol. 32, S. Ezekiel and H.J. Arditty, eds., Springer-Verlag, 1982, pp.157-162.
- V-14. Adamovsky, G.: All-Fibre Sensing Loop Using Pulse-Modulated Light-Emitting Diode. Electron. Lett., vol. 21, no. 20, Sept. 25, 1985, pp. 922-923.
- V-15. Adamovsky, G.: Time Domain Referencing in Intensity Modulation Fiber Optic Sensing Systems. Optical Testing and Metrology, C.P. Grover, ed., SPIE Proc. Vol. 661, Society of Photo-Optical Instrumentation Engineers, Bellingham, WA, 1986, pp. 145-151.
- V-16. Adamovsky, G.; and Piltch, N.D.: Fiber-Optic Thermometer Using Temperature Dependent Absorption, Broadband Detection, and Time Domain Referencing. Appl. Opt., vol. 25, no. 23, Dec. 1, 1986, pp. 4439-4443.
- V-17. Adamovsky, G.: Referencing in Fiber Optic Sensing Systems. Optical Techniques for Sensing and Measurement in Hostile Environments, C.H. Gillespie and R.A. Greenwell, eds., SPIE Proc. Vol. 787, SPIE, 1987, pp. 17-23.
- V-18. Adamovsky, G.: Amplitude Spectrum Modulation Technique for Analog Data Processing in Fiber Optic Sensing System with Temporal Separation of Channels. Fiber Optic and Laser Sensors V, R.P. De Paula and E. Udd, eds., SPIE Proc. Vol. 838, Society of Photo-Optical Instrumentation Engineers, Bellingham, WA, 1987, pp. 264-270.
- V-19. Adamovsky, G.: Fiber Optic Displacement Sensor with Temporally Separated Signal and Reference Channels. Appl. Opt., vol. 27, no. 7, Apr. 1, 1988, pp. 1313-1315.

- V-20. Adamovsky, G.; and Maitland, D.J.: Fiber Optic Sensors with Internal Referencing. Optical Testing and Metrology II, C.P. Grover, ed., SPIE Proc. Vol. 954, Society of Photo-Optical Instrumentation Engineers, Bellingham, WA, 1989, pp. 647-651. (NASA TM-100893.)
- V-21. Adamovsky, G.; and Maitland, D.J.: Fiber Optic Sensing Systems Using High Frequency Resonant Sensing Heads with Intensity Sensors. NASA TM-101318, 1988.
- V-22. Beheim, G.; and Fritsch, K.: Remote Displacement Measurements Using a Laser Diode. Electron. Lett., vol. 21, no. 3, Jan. 31, 1985, pp. 93-94.
- V-23. Beheim, G.; and Fritsch, K.: Range Finding Using Frequency-Modulated Laser Diode. Appl. Opt., vol. 25, no. 9, May 1, 1986, pp. 1439-1442.
- V-24. Beheim, G.; and Anthan, D. J.: Loss-Compensation of Intensity-Modulating Fiber-Optic Sensors. NASA TM-88825, 1986.
- V-25. Beheim, G.: Fiber-Optic Interferometer Using Frequency-Modulated Laser Diodes. Appl. Opt., vol. 25, no. 19, Oct. 1, 1986, pp. 3469-3472.
- V-26. Beheim, G.: Loss-Compensation Technique for Fiber-Optic Sensors and Its Application to Displacement Measurements. Appl. Opt., vol. 26, no. 3, Feb. 1, 1987, pp. 452-455.
- V-27. Beheim, G.; and Anthan, D.J.: Fiber-Optic Photoelastic Pressure Sensor with Fiber-Loss Compensation. Opt. Lett., vol. 12, no. 3, Mar. 1987, pp. 220-222.
- V-28. Beheim, G.; Fritsch, K.; and Poorman, R.N.: Fiber-Linked Interferometric Pressure Sensor. Rev. Sci. Instrum., vol. 58, no. 9, Sept. 1987, pp. 1655-1659.
- V-29. Mercer, C.R.; and Beheim, G.: Active Phase-Compensation System for Fiber Optic Holography. NASA TM-101295, 1988.
- V-30. Beheim, G., et al.: Modulated-Splitting-Ratio Fiber Optic Temperature Sensor. NASA TM-101332, 1988.
- V-31. Fritsch, K.; and Beheim, G.: Wavelength-Division Multiplexed Digital Optical Position Transducer. Opt. Lett., vol. 11, no. 1, Jan. 1986, pp. 1-3.
- V-32. Beheim, G.; and Fritsch, K.: Spectrum-Modulating Fiber-Optic Sensors for Aircraft Control Systems. NASA TM-88968, 1987.
- V-33. Beheim, G.: Fiber-Optic Thermometer Using Semiconductor-Etalon Sensor," Electron. Lett., vol. 22, no. 5, Feb. 27, 1986, pp. 238-239.
- V-34. Beheim, G.; Fritsch, K.; and Anthan, D.J.: Fiber-Optic Temperature Sensor Using a Spectrum-Modulating Semiconductor Etalon. NASA TM-100153, 1987.